Package: dispersionIndicators (via r-universe)

November 4, 2026

Title Indicators for the Analysis of Dispersion of Datasets with Batched and Ordered Samples

Version 0.2.0

Depends R (>= 4.1)

Description Provides methods for analyzing the dispersion of tabular datasets with batched and ordered samples. Based on convex hull or integrated covariance Mahalanobis, several indicators are implemented for inter and intra batch dispersion analysis. It is designed to facilitate robust statistical assessment of data variability, supporting applications in exploratory data analysis and quality control, for such datasets as the one found in metabololomics studies. For more details see Salanon (2024) <doi:10.1016/j.chemolab.2024.105148> and Salanon (2025) <doi:10.1101/2025.08.01.668073>.

URL https://forge.inrae.fr/pfem/dev/libs/dispersion_indicators

License MIT + file LICENSE

Encoding UTF-8

Suggests cli, pdftools, png, testthat (>= 3.0.0)

Imports corpcor, ggplot2 (>= 3.5.2), stats, utils, cowplot, qpdf

Config/testthat/edition 3

Collate convex_function.R icm_function.R

Config/roxygen2/version 8.1.1

NeedsCompilation no

Author Brice Mulot [aut], Elfried Salanon [ctb], Etienne Jules [aut, cre], INRAE (Institut national de recherche pour l'agriculture, l'alimentation et l'environnement) [cph]

Maintainer Etienne Jules <etienne.jules@inrae.fr>

Config/pak/sysreqs libjpeg-dev libssl-dev

Repository https://etiennejls.r-universe.dev

Date/Publication 2026-11-03 21:10:49 UTC

RemoteUrl https://github.com/cran/dispersionIndicators

RemoteRef HEAD

RemoteSha c89276368bb3e4611ebeadd90eabc3dbbd3787ed

Contents

calculate_convex_hull . . . 2
calculate_convex_indicators . . . 3
compute_icm_distances . . . 3
compute_individual . . . 4
compute_individual_batch . . . 5
compute_individual_global . . . 6
compute_inter . . . 6
compute_inter_batch_dispersion . . . 7
compute_intra . . . 7
compute_intra_batch_dispersion . . . 8
compute_ratio . . . 9
compute_shoelace_core . . . 9
convex_analysis_of_variables . . . 10
get_compact_order . . . 11
hull_data_list_check . . . 12
plot_all_convex_hulls . . . 12
plot_convex_hull . . . 13
save_icm_distances_csv . . . 14
shared_single_plot_convex_hulls . . . 14
single_variable_df_check . . . 15

Index **16**

`calculate_convex_hull` *Calculate Convex Hulls for one variable*

Description

Calculate Convex Hulls for one variable

Usage

```
calculate_convex_hull(data, var_name, impute_method = c("mean", "median"))
```

Arguments

`data`	Data frame containing the 'batch', 'order' and variable 'value' columns.
`var_name`	Name of the variable to calculate convex hull for.
`impute_method`	One of "mean" or "median".

Value

A list of dataframes of convex hull.

`calculate_convex_indicators` *Calculate the intra/inter batch dispersion indicators and their ratio on convex hulls of a single variable.*

Description

Calculate the intra/inter batch dispersion indicators and their ratio on convex hulls of a single variable.

Usage

```
calculate_convex_indicators(hull_data_list, var_name)
```

Arguments

`hull_data_list`	list of data frames of convex hulls.
`var_name`	name of the variable.

Value

A data frame with the indicators values.

`compute_icm_distances` *Compute ICM (Integrated Covariance Mahalanobis) Distances*

Description

This function computes Mahalanobis distances in PCA-reduced space, with options for individual, intra-group, and inter-group comparisons. It supports batch-wise analysis and shrinkage covariance estimation for robustness.

Usage

```
compute_icm_distances(
  data,
  batch_col = NULL,
  mode = c("individual", "intra", "inter", "all"),
  variance_threshold = 0.95,
  center_method_individual = c("global", "batch"),
  center_method_inter = c("mean", "median"),
  ref_batch = NULL
)
```

Arguments

data	A data.frame containing numeric variables and optionally a batch/group column.
batch_col	Name of the column representing batch or group (optional).
mode	Mode of computation: "individual", "intra", "inter", or "all".
variance_threshold	Threshold for cumulative variance to retain in PCA (default: 0.95).
center_method_individual	Method for centering in "individual" mode: "global" or "batch" (default: "global").
center_method_inter	Method for centering in "inter" mode: "mean" or "median" (default: "mean").
ref_batch	Reference batch name to compute inter-batch distances (default: first batch).

Value

A list containing data.frames of computed distances depending on the selected mode(s).

Examples

```
data <- data.frame(matrix(rnorm(100*5), ncol = 5))
data$Batch <- rep(c("A", "B", "C", "D"), each = 25)
result <- compute_icm_distances(
 data,
 batch_col = "Batch",
 mode = "all",
 center_method_individual = "batch",
 center_method_inter = "mean"
)
print(result)
```

---

compute_individual *Computes Integrated Covariance Mahalanobis (ICM) distances for individuals, in PCA-reduced space, against either global or batch-wise references.*

Description

Computes Integrated Covariance Mahalanobis (ICM) distances for individuals, in PCA-reduced space, against either global or batch-wise references.

Usage

```
compute_individual(pc_data, ref = c("global", "batch"), batch_col)
```

Arguments

pc_data	PCA-reduced data frame.
ref	Reference type: "global" for global barycenter, "batch" for batch-wise barycenters.
batch_col	Name of the column representing batch or group.

Value

A data frame with Mahalanobis distances for each individual against the specified reference.

---

compute_individual_batch

Computes Integrated Covariance Mahalanobis (ICM) distances of all individuals in PCA-reduced space, against their batch-wise barycenter reference.

Description

Computes Integrated Covariance Mahalanobis (ICM) distances of all individuals in PCA-reduced space, against their batch-wise barycenter reference.

Usage

```
compute_individual_batch(pc_data, batch_col)
```

Arguments

pc_data	PCA-reduced data frame.
batch_col	Name of the column representing batch or group.

Value

A data frame with Mahalanobis distances for each individual against their batch barycenter.

`compute_individual_global` *Computes Integrated Covariance Mahalanobis (ICM) distances of all individuals in PCA-reduced space, against their global barycenter reference.*

Description

Computes Integrated Covariance Mahalanobis (ICM) distances of all individuals in PCA-reduced space, against their global barycenter reference.

Usage

```
compute_individual_global(pc_data, batch_col)
```

Arguments

`pc_data`	PCA-reduced data frame.
`batch_col`	Name of the column representing batch or group.

Value

A data frame with Mahalanobis distances for each individual against the global barycenter.

`compute_inter` *Computes Integrated Covariance Mahalanobis (ICM) distances between batches barycenters in PCA-reduced space, using a reference bacth and either mean or median for center references.*

Description

Computes Integrated Covariance Mahalanobis (ICM) distances between batches barycenters in PCA-reduced space, using a reference bacth and either mean or median for center references.

Usage

```
compute_inter(
  pc_data,
  batch_col,
  ref_batch,
  center_method = c("mean", "median")
)
```

Arguments

pc_data	PCA-reduced data frame.
batch_col	Name of the column representing batch or group.
ref_batch	Name of the reference batch for distance computation.
center_method	Method for centering: "mean" or "median".

Value

A data frame with Mahalanobis distances for each batch against the reference.

---

compute_inter_batch_dispersion *Calculate the inter batch dispersion indicator on convex hulls of a single variable*

Description

Calculate the inter batch dispersion indicator on convex hulls of a single variable

Usage

```
compute_inter_batch_dispersion(hull_data_shoelace_list)
```

Arguments

hull_data_shoelace_list	named list of convex hulls data frames with an additional column of shoelace core

Value

value of inter batch dispersion.

---

compute_intra *Computes Integrated Covariance Mahalanobis (ICM) mean distances within each batch in PCA-reduced space, using median and mean for center references.*

Description

Computes Integrated Covariance Mahalanobis (ICM) mean distances within each batch in PCA-reduced space, using median and mean for center references.

Usage

```
compute_intra(pc_data, batch_col)
```

Arguments

pc_data	PCA-reduced data frame.
batch_col	Name of the column representing batch or group.

Value

A data frame with Mahalanobis distances mean for each batch.

---

compute_intra_batch_dispersion

Calculate the intra batch dispersion indicator on convex hulls of a single variable

---

Description

Calculate the intra batch dispersion indicator on convex hulls of a single variable

Usage

```
compute_intra_batch_dispersion(hull_data_shoelace_list)
```

Arguments

hull_data_shoelace_list	named list of convex hulls data frames with an additional column of shoelace core values, for each batch.

Value

value of intra batch dispersion.

`compute_ratio` *Calculate the intra/inter batch dispersion ratio indicator on convex hulls of a single variable.*

Description

Calculate the intra/inter batch dispersion ratio indicator on convex hulls of a single variable.

Usage

```
compute_ratio(intraB_disp, interB_disp)
```

Arguments

`intraB_disp`	value of intra batch dispersion indicator.
`interB_disp`	value of inter batch dispersion indicator.

Value

value of intra/inter batch dispersion ratio.

`compute_shoelace_core` *Compute the shoelace core for convex hulls of a single variable*

Description

Compute the shoelace core for convex hulls of a single variable

Usage

```
compute_shoelace_core(hull_data_list)
```

Arguments

`hull_data_list`	named list of data frames of convex hulls, for each batch.

Value

named list of dataframes of convex hull concatenated with a column of shoelace core values, for each batch.

convex_analysis_of_variables *Analyze a set of variables using convex hulls.*

Description

Analyze a set of variables using convex hulls.

Usage

```
convex_analysis_of_variables(
  data,
  variable_columns,
  batch_col = "batch",
  sample_order_col = "order",
  impute_if_needed = c("median", "mean"),
  mode = c("global", "batchwise")
)
```

Arguments

data	Data frame containing the data of multiple variable on multiple ordered and potentially batched sample.
variable_columns	Character vector of variable column names to analyse.
batch_col	Name of the column containing batch information.
sample_order_col	Name of the column containing the sample time order.
impute_if_needed	Method for imputing missing values, either "mean" or "median".
mode	Analysis mode, either "global" or "batchwise"

Value

A list containing the following elements:

- data: List of data frames for each variable.
- indicators: Data frame with convex hull indicators for each variable.
- convex_hulls: List of data frames of convex hulls for each varaible.

Examples

```
# Example usage on toy metabolomics data:
data <- data.frame(
  batch = rep(c("A","B","C"), each = 10),
  injectionOrder = rep(1:30, times = 1),
```

```
  metabolite1 = rnorm(30, mean = 100, sd = 10),
  metabolite2 = rnorm(30, mean = 200, sd = 20)
)
result <- convex_analysis_of_variables(
  data = data,
  variable_columns = c("metabolite1", "metabolite2"),
  batch_col = "batch",
  sample_order_col = "injectionOrder",
  impute_if_needed = "median",
  mode = "global"
)
plot_all_convex_hulls(
  target_file_path = file.path(tempdir(), "convex_hulls.pdf"),
  convex_analysis_res = result,
  show_points = TRUE,
  mode = "global"
)
```

`get_compact_order` *Get the compact order for a data frame of batches and orders of samples.*

Description

Get the compact order for a data frame of batches and orders of samples.

Usage

```
get_compact_order(batch_order_df)
```

Arguments

`batch_order_df`	Data frame containing the batch and order columns of samples.

Details

Compact orders conserve the original order but are limited to gaps of 1 for two consecutive intra-batch samples and gaps of 2 for two consecutive inter-batch samples.

Value

A data frame with the compact order values.

hull_data_list_check *Function to check if hull_data_list is a valid list of data frames*

Description

Function to check if hull_data_list is a valid list of data frames

Usage

```
hull_data_list_check(hull_data_list, name)
```

Arguments

hull_data_list	List of data frames representing convex hulls.
name	Name of the hull_data_list for error messages.

Value

None. The function raises an error if the checks fail.

plot_all_convex_hulls *Plot all convex hulls for each variable in a PDF file.*

Description

Plot all convex hulls for each variable in a PDF file.

Usage

```
plot_all_convex_hulls(
  target_file_path,
  convex_analysis_res,
  show_points,
  mode = c("global", "batchwise"),
  use_compact_order = FALSE
)
```

Arguments

target_file_path	Path to the output PDF file.
convex_analysis_res	Result of the convex analysis containing data, convex hulls and indicators.
show_points	Boolean indicating whether to show points in the plot.
mode	Mode of the analysis, either "global" or "batchwise".

use_compact_order
: Boolean indicating whether to compact hulls on the order axis in case the order in the data is very sparse.

Value

None. The function saves the plots to a PDF file.

---

plot_convex_hull *Plot the convex hulls of a single variable.*

Description

Plot the convex hulls of a single variable.

Usage

```
plot_convex_hull(
  data,
  hull_data_list,
  var_name,
  show_points,
  label_prefix,
  indicators
)
```

Arguments

data	Data frame containing the batch, order and variable value columns.
hull_data_list	List of data frames of convex hulls.
var_name	Name of the variable.
show_points	Boolean indicating whether to show points.
label_prefix	Prefix for the plot title.
indicators	Data frame with the indicators values.

Value

A ggplot object.

save_icm_distances_csv *Save ICM Distances to CSV Files*

Description

Save ICM Distances to CSV Files

Usage

```
save_icm_distances_csv(distances, folder_path, prefix = "ICM")
```

Arguments

distances	A list containing data.frames of distances (result from compute_icm_distances)
folder_path	Path to the folder where files will be saved.
prefix	Prefix for the output file names.

Value

None. Saves files to folder_path.

shared_single_plot_convex_hulls *Plot convex hulls from multiple variables on a single shared plot.*

Description

Plot convex hulls from multiple variables on a single shared plot.

Usage

```
shared_single_plot_convex_hulls(
  convex_analysis_res,
  target_file_path,
  show_points,
  standardize_per_variable = FALSE,
  use_compact_order = FALSE
)
```

Arguments

convex_analysis_res	Result of the convex analysis containing data, convex hulls and indicators.
target_file_path	Path to the output PDF file.
show_points	Boolean indicating whether to show data points.
standardize_per_variable	Boolean indicating whether to standardize (z-score) the values per variable.
use_compact_order	Boolean indicating whether to compact hulls on the order axis in case the order in the data is very sparse.

Value

None. The function saves the plot to a PDF file.

---

single_variable_df_check

Function to check if a single variable data frame is valid

Description

Function to check if a single variable data frame is valid

Usage

```
single_variable_df_check(df, name)
```

Arguments

df	Data frame containing 'batch', 'order', and 'value' columns.
name	Name of the data frame for error messages.

Value

None. The function raises an error if the checks fail.

Index

calculate_convex_hull, 2
calculate_convex_indicators, 3
compute_icm_distances, 3
compute_individual, 4
compute_individual_batch, 5
compute_individual_global, 6
compute_inter, 6
compute_inter_batch_dispersion, 7
compute_intra, 7
compute_intra_batch_dispersion, 8
compute_ratio, 9
compute_shoelace_core, 9
convex_analysis_of_variables, 10

get_compact_order, 11

hull_data_list_check, 12

plot_all_convex_hulls, 12
plot_convex_hull, 13

save_icm_distances_csv, 14
shared_single_plot_convex_hulls, 14
single_variable_df_check, 15